



Width A (mm)	Height B (mm)	Depth C (mm)	Enclosures Reference No	Sizes						Weight (kg)
				D (mm)	E (mm)	F (mm)	G (mm)	K (mm)	L (mm)	
400	1800	400	BSE 041840	240	1780	195	350	302	1702	78
		500	BSE 041850	340	1780	295	450	302	1702	85
		600	BSE 041860	440	1780	395	550	302	1702	92
		800	BSE 041880	640	1780	595	750	302	1702	105
	2000	400	BSE 042040	240	1980	195	350	302	1902	86
		500	BSE 042050	340	1980	295	450	302	1902	93
		600	BSE 042060	440	1980	395	550	302	1902	100
		800	BSE 042080	640	1980	595	750	302	1902	114
600	1800	400	BSE 061840	240	1780	195	350	502	1702	99
		500	BSE 061850	340	1780	295	450	502	1702	106
		600	BSE 061860	440	1780	395	550	502	1702	114
		800	BSE 061880	640	1780	595	750	502	1702	128
	2000	400	BSE 062040	240	1980	195	350	502	1902	108
		500	BSE 062050	340	1980	295	450	502	1902	116
		600	BSE 062060	440	1980	395	550	502	1902	123
		800	BSE 062080	640	1980	595	750	502	1902	139
800	1800	400	BSE 081840	240	1780	195	350	702	1702	120
		500	BSE 081850	340	1780	295	450	702	1702	127
		600	BSE 081860	440	1780	395	550	702	1702	135
		800	BSE 081880	640	1780	595	750	702	1702	151
	2000	400	BSE 082040	240	1980	195	350	702	1902	130
		500	BSE 082050	340	1980	295	450	702	1902	138
		600	BSE 082060	440	1980	395	550	702	1902	147
		800	BSE 082080	640	1980	595	750	702	1902	163

Characteristics :

- Galvanized sheet steel enclosure : 1.5 mm
- door : 2 mm
- mounting plate : 2 mm
- plinth : 2 mm
- Foamed-in door sealing gasket.
- Conductive spring clips all around front door and back cover.
- EMC gasketed side panels, top cover and plinth.
- Conductive interior surface.
- Concealed hinges.
- Double level mounting ability.
- High protection (IP 55).
- Powder coating (RAL 7032w).
- Galvanized mounting plate.
- Swing-handle Rod-Latch lock system.

EMC SHIELDED ENCLOSURES

