

Characteristics

- Material**
Galvanized Steel (EN 10346 DX51D+Z)
- Frame : 1.5 mm
 - Panel : 1.5 mm
 - Door : 2 mm
 - Plinth : 2 mm
 - Mounting plate : 2 mm
- Surface Finishing**
■ RAL7035w powder coated outer surface
- IP Rating**
■ IP55 (TS 3033, EN 60529)
- Others**
- EMC gasketed front door and rear panel
 - EMC gasketed side panels, top cover and plinth
 - Conductive interior surface
 - Swing-handle polyamide lock (4 points locking, 333 key)
 - Concealed hinge
 - Multiple mounting plate possibility



On Request

- Special sizes
- Special colour
- Pre-punching



Supply Includes

- Front and rear frame
- Door
- Rear panel
- Mounting plate
- Plinth
- Top cover
- Side panels
- 4/6 pcs side rails
- Door inside mounting profile

Complementary Accessories

- Eye bolt
- Rain canopy
- Door inside mounting profile
- Short mounting plate
- Partial mounting plate
- Carriage depth slide and support
- Partition profile
- L, U and Z profiles
- L and Z brackets
- Busbar & depth profile
- Ladder busbar profile
- Plan pocket
- Earthing cable

Width A	Height B	Depth C	Reference	Door pcs	Lock Type	Hinge pcs	Side Panel		Mounting Plate		Weight kg
							↔	↕	↔	↕	
mm	mm	mm					mm	mm	mm	mm	
400	1800	400	BSE 041840	1	I	3	240	1780	302	1702	78
		500	BSE 041850	1	I	3	340	1780	302	1702	85
		600	BSE 041860	1	I	3	440	1780	302	1702	92
		800	BSE 041880	1	I	3	640	1780	302	1702	105
	2000	400	BSE 042040	1	I	3	240	1980	302	1902	86
		500	BSE 042050	1	I	3	340	1980	302	1902	93
		600	BSE 042060	1	I	3	440	1980	302	1902	100
		800	BSE 042080	1	I	3	640	1980	302	1902	114
600	1800	400	BSE 061840	1	I	3	240	1780	502	1702	99
		500	BSE 061850	1	I	3	340	1780	502	1702	106
		600	BSE 061860	1	I	3	440	1780	502	1702	114
		800	BSE 061880	1	I	3	640	1780	502	1702	128
	2000	400	BSE 062040	1	I	3	240	1980	502	1902	108
		500	BSE 062050	1	I	3	340	1980	502	1902	116
		600	BSE 062060	1	I	3	440	1980	502	1902	123
		800	BSE 062080	1	I	3	640	1980	502	1902	139
800	1800	400	BSE 081840	1	I	3	240	1780	702	1702	120
		500	BSE 081850	1	I	3	340	1780	702	1702	127
		600	BSE 081860	1	I	3	440	1780	702	1702	135
		800	BSE 081880	1	I	3	640	1780	702	1702	151
	2000	400	BSE 082040	1	I	3	240	1980	702	1902	130
		500	BSE 082050	1	I	3	340	1980	702	1902	138
		600	BSE 082060	1	I	3	440	1980	702	1902	147
		800	BSE 082080	1	I	3	640	1980	702	1902	163

