

Characteristics

Material

- Sheet Steel (EN 10130 DC01)
  - Body : 1.5 mm
  - Door : 2 mm
  - Plinth : 2 mm
- Galvanized Steel (EN 10346 DX51D+Z)
  - Mounting plate : 2 mm

Surface Finishing

- RAL7035w powder coating

IP Rating

- IP65 (TS 3033, EN 60529)

Others

- Welded frame construction
- Foamed-in door PU sealing gasket
- Swing-handle polyamide lock (3 points locking, 333 key)
- Concealed hinge
- Plinth and cover options



On Request

- Special sizes
- Special colour
- Pre-punching
- Special mounting plate



Supply Includes

- Body
- Door and rear panel
- Mounting plate
- Plinth
- 4/6 pcs side rails
- Rain canopy

Complementary Accessories

- Side rail
- Short mounting plate
- Partial mounting plate
- Carriage depth slide and support
- Z profile
- Busbar & depth profile
- Ladder busbar profile
- Door inside mounting profile
- Partition profile
- Eye bolt

Width	Height	Depth	Reference	Door	Hinge	Mounting Plate Dimensions	
						↔	↕
A	B	C		pcs	pcs	mm	mm
600	1200	600	CC 061260	1	3	502	1102
	1500	600	CC 061560	1	3	502	1402
800	1200	600	CC 081260	1	3	702	1102
	1500	600	CC 081560	1	3	702	1402

