

Characteristics

- Material**
Stainless Steel 304L (EN 10088 1.4307)
- Body : 1.2 mm
 - Door : 1.2 mm
- Surface Finishing**
- Scotch-brite brushed
- IP Rating**
- IP55 (TS 3033, EN 60529)
- Others**
- Left and right handles
 - Foamed-in rear door PU sealing gasket
 - Hinged lockable rear door
 - Top cable entry



On Request

- Special sizes
- Special mounting plate
- Pre-punching
- 316L Grade SS

Supply Includes

- Body
- Lockable rear door
- Handles

Complementary Accessories

- Earthing cable
- DIN rail



STAINLESS STEEL ENCLOSURES

STAINLESS STEEL ENCLOSURES



Width A	Height B	Depth C	Reference	Useful Area Side		Rear Door		Front Useful Area		Cable Gland (Top)	
				mm	mm	mm	mm	mm	mm	# pcs	∅ mm
300	300	160	SSKPA 030316	300	117	210	260	290	300	1	40
	400	160	SSKPA 030416	400	117	210	360	290	400	1	40
400	400	160	SSKPA 040416	400	117	310	360	390	400	1	40
	500	160	SSKPA 040516	500	117	310	460	390	500	1	40
500	500	160	SSKPA 050516	500	117	410	460	490	500	1	40

