

Characteristics

- Material**
 Sheet Steel (EN 10130 DC01)
 ■ Body : 1.2 / 1.5 mm
 ■ Glazed door : 1.2 / 1.5 mm
- Surface Finishing**
 ■ RAL7035w powder coating
- IP Rating**
 ■ IP65 (TS 3033, EN 60529)
- Others**
 ■ Glazed / Solid / Perforated door
 ■ Foamed-in door PU sealing gasket
 ■ Bottom & top plain gland plate
 ■ 155° concealed hinges
 ■ 5mm Double-bit insert polyamide lock



On Request

- Special sizes
- Special colour
- Pre-punching

Supply Includes

- Body
- Glazed door
- Bottom & top plain gland plate
- 2 pcs depth adjustable 19" profiles
- 4/6 pcs wall brackets

Complementary Accessories

- Perforated / solid door
- Vented dust protection hood
- Plinth
- Levelling feet
- Castor
- Top and bottom filter fitted, fan fitted, brushed, perforated cover plates
- Power distribution unit
- 19" pull out perforated shelf
- Mounting plate
- Telescopic slide
- Locks
- Earthing cable
- 19" equipment shelf
- Patch panel and 1U fan unit
- Cable organizer



Height units	Width			Reference	Lock	Hinge	Apparent Area		Wall Mounting		Weight
	A	B	C				↔	↕	↔	↕	
U*	mm	mm	mm		pcs	pcs	mm	mm	mm	mm	kg
7 U	600	360	400	MR 060740	1	2	436	210	624	308	16.5
9 U	600	445	400	MR 060940	1	2	436	295	624	393	19.0
12 U	600	580	400	MR 061240	2	2	436	430	624	528	22.5
18 U	600	845	400	MR 061840	2	3	436	695	624	793	28.5
26 U	600	1200	400	MR 062640	2	4	436	1050	624	1148	36.5

* 1U = 44.45 mm

