

Characteristics

- Busbar (TEMBAR series) installed enclosure for ready to assembly (without main switch)
- Earth and shrouded neutral terminals
- Adjustable fixing parts for most major manufacturers standard (2A to 63A) MCB's
- Sheet steel enclosure, door and cover
- Built-in design
- Foamed-in door PU sealing gasket
- Top and bottom gland plates
- 155° concealed hinges
- Door can be left or right handed
- Colour coding for all connections as standard
- RAL7035w powder coating

On Request

- Special colour
- Special mounting plate
- Special sizes
- Glazed door
- Pre-punching



Incoming Current	Pole	Outgoing Terminal Centres	Way	Reference	Width	Height	Depth
					A	B	C
A		mm			mm	mm	mm
250	2	18	6	TDK S 01 2P 06 18	420	655	150
	2		12	TDK S 01 2P 12 18			
	3		6	TDK S 01 3P 06 18			
	3		8	TDK S 01 3P 08 18			
250	4	18	6	TDK S 01 4P 06 18	420	755	150
	2		18	TDK S 02 2P 18 18			
	3		10	TDK S 02 3P 10 18			
	3		12	TDK S 02 3P 12 18			
250	2	18	24	TDK S 03 2P 24 18	420	855	150
	3		14	TDK S 03 3P 14 18			
	3		16	TDK S 03 3P 16 18			
	4		12	TDK S 03 4P 12 18			
250	2	18	30	TDK S 04 2P 30 18	420	955	150
	3		18	TDK S 04 3P 18 18			
	3		20	TDK S 04 3P 20 18			
250	2	18	36	TDK S 05 2P 36 18	420	1055	150
	3		22	TDK S 05 3P 22 18			
	3		24	TDK S 05 3P 24 18			
	4		18	TDK S 05 4P 18 18			